

IMPORTANT FEATURES

INTERNAL WRAPPING UNIT

First stage internal wrapping
Programmable no. of internal layers
UV protected wrapping film
520 mm film roll

OPERATOR PLATFORM

Elevated platform for operator
Easy monitoring of all operation

HOPPER & CONVEYOR SYSTEM

Hopper capacity up to 600 kg
Sufficient up to 6-7 bales
Conveyer capacity: 125 kg/min
Chain operated system

COMPRESSION CHAMBER

Compaction rate: 650 kg/m³
Automatic pressure control

EXTERNAL WRAPPING UNIT

Programmable no. of layers
Automatic bale count
Automatic bale ejection

DIGITAL CONTROL PANEL

Easy operation
Programmable internal & external wrapping layers
Set desired bale weight (b/w 90 kg to 115kg)
Optional manual control



TECHNICAL SPECIFICATIONS

PARAMETER	ASB 100	ASB 60
Machine Width	6.50 feet	
Machine Length	16.0 feet	
Machine Height	7.50 feet	
Machine Total Weight	3,300 kg	
Hopper Capacity	600 kg	
Operation System	Digital Controller with Alphanumeric Display (DC 12V)	
Power Source	Tractor 35 HP PTO at 540 RPM or 20 HP Electric Motor (3Phase Power Supply)	
Compaction Density	650 kg/cm ³	
Bale Chamber Diameter	550 mm x 500mm	550mm x 450mm (H x W)
Bale Weight	90 to 110 kg	60 to 80 kg
Bales Capacity	50 to 60 bales per hour	
External Wrapping (Horizontal)	250 mm	
Internal Wrapping (Vertical)	500 mm	
Wrapping Film	25 microns	
Hydraulic Pump	20 litre (single pump)	
Hydraulic Motor	1 For External Wrapping	
Hydraulic Distributor	7 Double Action 12V Distributor	
Hydraulic Oil Tank	26 litre	
Conveyor	Yes (Chain Type)	
Tyre	2 tyres	
Warning System	Alarm and Red Light	
Roller Support System	Bearings; Manual greased	
Controller Power Source	12V Alternator	

