



Chassis Type	5 m³		6 m³		8 m³		10 m³		12 m³		14 m³		16 m³	18 m³	20 m³
	Low Chassis	High Chassis	Low Chassis	High Chassis	Low Chassis	High Chassis	Low Chassis	High Chassis	Low Chassis	High Chassis	Low Chassis	High Chassis	Coming Soon	Coming Soon	Coming Soon
Length-A (mm)	4580	4580	4930	4930	5060	5060	5900	5900	6350	6350	6670	6670	Coming Soon	Coming Soon	Coming Soon
Height-B (mm)	2200	2305	2200	2305	2350	2490	2450	2590	2530	2670	2650	2790	Coming Soon	Coming Soon	Coming Soon
Width-C (mm)	1865	1735	1865	1735	2135	2025	2230	2105	2230	2105	2230	2105	Coming Soon	Coming Soon	Coming Soon
Wheel Trail Width-D (mm)	1571	1451	1571	1451	1806	1671	1806	1671	1806	1671	1806	1671	Coming Soon	Coming Soon	Coming Soon
Conveyor Closed Width-E (mm)	2410	2350	2410	2350	2585	2530	2635	2571	2635	2571	2635	2571 m	Coming Soon	Coming Soon	Coming Soon
Conveyor Open Width-F (mm)	1950	1895	1950	1895	2115	2100	2215	2150	2215	2150	2215	2150	Coming Soon	Coming Soon	Coming Soon
Capacity (Net Volume)	5 m³		6 m³		8 m³		10 m³		12 m³		14 m³		Coming Soon	Coming Soon	Coming Soon
Empty Weight	2810 kg		3000 kg		3550 kg		4000 kg		4450 kg		4710 kg		Coming Soon	Coming Soon	Coming Soon
Maximum Loaded Weight	4310 kg		4800 kg		5950 kg		7000 kg		8050 kg		8910 kg		Coming Soon	Coming Soon	Coming Soon
Power Requirement (PTO)	54HP		60HP		70HP		80HP		90HP		105HP		Coming Soon	Coming Soon	Coming Soon
PTO Speed	540 rpm		540 rpm		540 rpm		540 rpm		540 rpm		540 rpm		Coming Soon	Coming Soon	Coming Soon
Wheel Sizes	10.0/75-15.3		10.0/75-15.3		12.5/80-15.3		400/60-15.5		400/60-15.5		400/60-15.5		Coming Soon	Coming Soon	Coming Soon
The quantity of Knives	54 pcs		64 pcs		88 pcs		110 pcs		132 pcs		144 pcs		Coming Soon	Coming Soon	Coming Soon
The quantity of Load Cells	3 pcs		3 pcs		3 pcs		3 pcs		3 pcs		3 pcs		Coming Soon	Coming Soon	Coming Soon
Weight System	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
High Level Chassis System	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Low Level Chassis System	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Feed Discharge Right Side	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Feed Discharge Left Side	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Feed Discharge Window	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Right Feed Discharge Conveyor	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Left Feed Discharge Conveyor	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Mechanical Lifting	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Hydraulic Lifting	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Ladder	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Sliding Hydraulic Control System	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Wired Hydraulic Control System	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Bagging Kit	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Back Cover	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Back Loading Bucket	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon
Transmission PTO Double Outlet	Standard		Standard		Standard		Standard		Standard		Standard		Coming Soon	Coming Soon	Coming Soon
Transmission + Blackbox PTO Double Outlet	Optional		Optional		Optional		Optional		Optional		Optional		Coming Soon	Coming Soon	Coming Soon

BRASSUS MICRO		2 m³		3 m³		4 m³		5 m³	
Chassis Type	Trailer type	Stationary type	Trailer type	Stationary	Trailer type	Stationary	Mobile	Stationary	
Length-A	3365 mm	2425 mm	3740 mm	2810 mm	4015 mm	3100 mm	4515 mm	3580 mm	
Height-B	1690 mm	1820 mm	1865 mm	2010 mm	2065 mm	2195 mm	2150 mm	2195 mm	
Width-C	1440 mm	1465 mm	1470 mm	1490 mm	1490 mm	1500 mm	1585 mm	1500 mm	
Wheel Trail Width-D	1264 mm	-	1274 mm	-	1272 mm	-	1300 mm	-	
Feed Discharge Width-E	1475 mm	-	1540 mm	-	1550 mm	-	1600 mm	-	
Auger Core Thickness	8 mm	8 mm	8 mm	8 mm	10 mm	10 mm	10 mm	10 mm	
Auger Stripe Thickness	10 mm	10 mm	10 mm	10 mm	12 mm	12 mm	12 mm	12 mm	
Side Wall Thickness	4 mm	4 mm	4 mm	4 mm	4 mm	4 mm	4 mm	4 mm	
Front Wall Thickness	4 mm	4 mm	4 mm	4 mm	4 mm	4 mm	4 mm	4 mm	
Floor Plate Thickness	8 mm	8 mm	8 mm	8 mm	8 mm	8 mm	8 mm	8 mm	
Empty Weight		850 kg	1065 kg	1015 kg	1250 kg	1160 kg	1450 kg	1350 kg	
Loading Capacity	600 kg	600 kg	900 kg	900 kg	1200 kg	1200 kg	1500 kg	1500 kg	
The quantity of Knives	26 pcs	26 pcs	36 pcs	36 pcs	52 pcs	52 pcs	68 pcs	68 pcs	
Wheel size	165/80-R13-PT311	-	175/65-R14-PT311	-	185/65-R14-PT311	-	10.0/75-15.3-12RF	-	
Rim	4.00X13-B4	-	5.50X14-B5	-	5.50X14-B5	-	9.00X15.3	-	
Tractor PTO Speed	540 RPM	540 RPM	540 RPM	540 RPM	540 RPM	540 RPM	540 RPM	540 RPM	
Tractor PTO Power Requirement	Min 20 hp	Min 20 hp	Min 25 hp	Min 25 hp	Min 30 hp	Min 30 hp	Min 40 hp	Min 40 hp	
Electricity Engine Power Requirement	11 Kw - 1500 d/dk	11 Kw - 1500 d/dk	15 Kw - 1500 d/dk	15 Kw - 1500 d/dk	18.5 Kw - 1500 d/dk	18.5 Kw - 1500 d/dk	22 Kw - 1500 d/dk	22 Kw - 1500 d/dk	
Mobile Chassis	Standard	-	Standard	-	Standard	-	Standard	-	
Stationary Chassis	-	Standard	-	Standard	-	Standard	-	Standard	
Weight System	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Transmission PTO Single Outlet	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Transmission PTO Double Outlet	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Transmission + Blackbox PTO Double Outlet	Optional	Standard	Optional	Standard	Optional	Standard	Optional	Standard	
Feed Discharge Side Right	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Feed Discharge Side Left	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Hydraulic Feed Discharge Cover	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Mechanical Feed Discharge Cover	Optional	Standard	Optional	Standard	Optional	Standard	Optional	Standard	
Feed Discharge Plate	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Hydraulic Feed Discharge Conveyor	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Electricity Feed Discharge Conveyor	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Conveyor Bagging Kit	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Tractor Independent Hydraulic	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Tractor Dependant Hydraulic	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Sliding Hydraulic Control System	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Wired Hydraulic Control System	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Back Load Half Cover	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Back Load Bucket	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
Mechanical Foot Jack	Standard	-	Standard	-	Standard	-	Standard	-	

1m³ FEED = 300 KG (60% OF THE RATION CONTENT IS CALCULATED AS HIGH QUALITY COARSE FODDER.) WEIGHT OF THE MACHINE MAY VARY ACCORDING TO THE OPTIONS CHOSEN. ÇELİKEL TARIM LTD. ŞTİ. KEEPS CHANGING OF TECHNICAL VALUE RIGHTS RESERVED.