

# CHARGER

	16m <sup>3</sup>	18m <sup>3</sup>	20m <sup>3</sup>	22m <sup>3</sup>	16m <sup>3</sup> STATIONARY	18m <sup>3</sup> STATIONARY	20m <sup>3</sup> STATIONARY	22m <sup>3</sup> STATIONARY
Length- ( A )	7600 mm	7600 mm	7600 mm	7890 mm	7600 mm	7600 mm	7600 mm	7890 mm
Width- ( B )	2225 mm	2225 mm	2225 mm	2225 mm				
Height- ( C )	2525 mm	2600 mm	2735 mm	2800 mm	2525 mm	2600 mm	2735 mm	2800 mm
Maximum Loaded Weight	11100 Kg	12000 Kg	12700 Kg	13350 Kg	11100 Kg	12000 Kg	12700 Kg	13350 Kg
Empty Weight	6250 Kg	6500 Kg	6690 Kg	6725 Kg	6250 Kg	6500 Kg	6690 Kg	6725 Kg
PTO Speed	540 rpm	540 rpm	540 rpm	540 rpm				
WHEEL Size	4 x 215/70/R17.5	4 x 215/70/R17.5	4 x 215/70/R17.5	4 x 215/70/R17.5				
Power Requirement	90 Hp	95 Hp	110 Hp	110 Hp	90 Hp	95 Hp	110 Hp	110 Hp
Weighing System Load Cell Number	3 Pcs	3 Pcs	3 Pcs	3 Pcs				
Auger Knife Number	2 x 6 Pcs	2 x 6 Pcs	2 x 6 Pcs	2 x 6 Pcs				
Fixed Knife Number	2 Pcs	2 Pcs	2 Pcs	2 Pcs				
Ladder	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Front Discharge Cover	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Back Discharge Cover	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Right Cross Discharge Cover	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Right Front Cross and Left Front Cross	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Discharge Covers	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Bagging Kit	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Weighing System	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Loading Bucket System	-	-	-	-	-	-	-	-
Electricity Engine	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Double Speed (Shift) Reductor	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Discharge Cover	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Independent Hydraulic System	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Conveyor Band	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Magnet	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Tractor Mount Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type
Axle System with Brakes	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Warning Light	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Marker Lamps	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional

1m<sup>3</sup> FEED = 300 KG (60% OF THE RATION CONTENT IS CALCULATED AS HIGH QUALITY COARSE FODDER.) WEIGHT OF THE MACHINE MAY VARY ACCORDING TO THE OPTIONS CHOSEN. ÇELİKEL TARIM LTD. ŞTİ. KEEPS CHANGING OF TECHNICAL VALUE RIGHTS RESERVED

<b>CHARGER MICRO</b>		0.75m <sup>3</sup>	2m <sup>3</sup> V1 (TOW TYPE)	2m <sup>3</sup> V2 (STATIONARY)	2m <sup>3</sup> V3 (STATIONARY)	2m <sup>3</sup> A1 (TOW TYPE)	3m <sup>3</sup>	4m <sup>3</sup>	5m <sup>3</sup>	6m <sup>3</sup>	8m <sup>3</sup>	10m <sup>3</sup>	12m <sup>3</sup>	14m <sup>3</sup>
Length- ( A )		1500 mm	3875 mm	2070 mm	1960 mm	3875 mm	4485 mm	4485 mm	4810 mm	4810 mm	5200 mm	5200 mm	5200 mm	5200 mm
Width- ( B )		1500 mm	1680 mm	1920 mm	1450 mm	1800 mm	1850 mm	1850 mm	2115 mm	2115 mm	2300 mm	2300 mm	2300 mm	2300 mm
Height- ( C )		1490 mm	1750 mm	1640 mm	1640 mm	1750 mm	2000 mm	2350 mm	2235 mm	2500 mm	2400 mm	2720 mm	3000 mm	3280 mm
Maximum Loaded Weight		605 Kg	1570 Kg	1260 Kg	1170 Kg	1640 Kg	2140 Kg	2520 Kg	3100 Kg	3540 Kg	6785 Kg	7720 Kg	8655 Kg	9590 Kg
Empty Weight		380 Kg	970 Kg	660 Kg	570 Kg	1040 Kg	1240 Kg	1320 Kg	1600 Kg	1740 Kg	4385 Kg	4720 Kg	5055 Kg	5400 Kg
PTO Speed		540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Wheel Sizes		4 x (M131-121-150)	2 x 185R14C	-	-	2 x 185R14C	2 x 10.0/75-15,3	2 x 10.0/75-15,3	2 x 10.0/75-15,3	2 x 10.0/75-15,3	2 x 12.5/80-15,3	2 x 12.5/80-15,3	2 x 12.5/80-15,3	2 x 12.5/80-15,3
Power Requirements		220V-3kW/4Hp	35Hp	380 V - 7.5kw/10Hp	35Hp	380 V - 7.5 kw/10Hp	40 Hp	40 Hp	50-55 Hp	50-55 Hp	48 Kw / 65 Hp	48 Kw / 65 Hp	59 Kw / 80 Hp	80 Hp
Power Source		Electricity + PTO	PTO	Electricity + PTO	PTO	Electricity + PTO	PTO	PTO	PTO	PTO	PTO	PTO	PTO	PTO
Weighing System Load Cell Number		-	-	-	-	-	3 Pcs							
Auger Knife Number		4 Pcs	5 Pcs	5 Pcs	5 Pcs	5 Pcs	6 Pcs	6 Pcs	7 Pcs	7 Pcs	6 Pcs	6 Pcs	6 Pcs	6 Pcs
Fixed Knife Number		-	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs	2 Pcs
Ladder		-	-	-	-	-	-	-	-	-	Optional	Optional	Optional	Optional
Right Side Discharge Cover		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Left Side Discharge Cover		Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Front Discharge Cover		-	-	-	-	-	-	-	-	-	Optional	Optional	Optional	Optional
Back Discharge Cover		-	-	-	-	-	-	-	-	-	Optional	Optional	Optional	Optional
Right and Left Side Discharge Cover		-	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Right Cross Discharge Cover		-	-	-	-	-	-	-	-	-	Standard	Standard	Standard	Standard
Right Front Cross and Left Front Cross		-	-	-	-	-	-	-	-	-	Optional	Optional	Optional	Optional
Discharge Cover		-	-	-	-	-	-	-	-	-	Optional	Optional	Optional	Optional
Bagging Kit		Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Weighing System		-	-	-	-	-	Optional							
Loading Bucket System		-	Optional	-	-	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Electric Engine		Standard	-	Standard	-	Standard	Optional							
Discharge Cover		Manual	Hydraulic	Manual	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Independent Hydraulic		-	Optional	-	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Conveyor Band		-	-	-	-	-	Optional							
Magnet		Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Tractor Mount Type		3 Aski	Tow Type	3 points linkage system + Stationary type	3 points linkage system + Stationary type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type	Tow Type
Warning Light		Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Marker Lamps		-	-	-	-	-	-	-	-	-	Standard	Standard	Standard	Standard