

CALABRIA	DOUBLE CHOP 1500	DOUBLE CHOP 1800	DOUBLE CHOP 2100
POWER REQUIREMENT (MIN – MAX)	45 – 60 kW	60 – 80 kW	80 – 100 kW
WORKING WIDTH	1500 mm	1800	2100
ROTOR KNIFE NUMBER	36 pcs	48 pcs	56 pcs
CHOPPING KNIFE NUMBER	10 pcs	10 pcs	10 pcs
SWEEPING PADDLE NUMBER	10 pcs	10 pcs	10 pcs
WHEEL SIZES	165X70XR13	165X70XR13	165X70XR13
ROTOR REV NUMBER	2250 RPM	2250 RPM	2250 RPM
CHOPPING KNIFE REV NUMBER	1620 RPM	1620 RPM	1620 RPM
WEIGHT	925 KG	975 KG	1045 KG
PTO REV NUMBER	540 RPM	540 RPM	540 RPM
WORK CAPACITY *	20 ton / hr	25 ton / hr	30 ton / hr
WIDTH (WORK POSITION)	2535 mm	2835 mm	3135 mm
HEIGHT (WORK POSITION)	3700 mm	3700 mm	3700 mm
LENGHT (WORK POSITION)	2400 mm	2400 mm	2400 mm
WIDTH (ROAD POSITION)	2540 mm	2840 mm	3140 mm
HEIGHT (ROAD POSITION)	2355 mm	2355 mm	2355 mm
LENGTH (ROAD POSITION)	3170 mm	3170 mm	3170 mm
CHOPPING SIZE (ADJUSTABLE)	20 – 70 mm	20 – 70 mm	20 – 70 mm
REAPING HEIGHT (ADJUSTABLE)	50-150 mm	50-150 mm	50-150 mm

CHALLENGER

AVERAGE SILAGE YIELD IS CONSIDERED AS 7500. IT MAY VARY DEPENDING ON THE OPERATOR EXPERIENCE AND FIELD CONDITIONS.
AVERAGE SILAGE YIELD IS CONSIDERED AS 7500. IT MAY VARY DEPENDING ON THE OPERATOR EXPERIENCE AND FIELD CONDITIONS.
ARE TRACTOR PTO VALUES.
*** ARE AVERAGE VALUES. IT MAY VARY DEPENDING ON THE HUMIDITY AND THE TYPE OF THE PRODUCT.

TECHNICAL FEATURE VALUES ARE VALID AFTER THE DATE OF RELEASE. ÇELİKEL TARIM LTD. ŞTİ. KEEPS CHANGING OF TECHNICAL VALUE RIGHTS RESERVED WITHOUT THE NECESSITY OF A PUBLIC DECLARATION.
TECHNICAL FEATURE VALUES ARE VALID AFTER THE DATE OF RELEASE. ÇELİKEL TARIM LTD. ŞTİ. KEEPS CHANGING OF TECHNICAL VALUE RIGHTS RESERVED WITHOUT THE NECESSITY OF A PUBLIC DECLARATION.

CALABRIA

* IT MAY VARY DEPENDING ON THE PRODUCT TYUPE AND YIELD, FIELD CONDITIONS AND OPERATOR EXPERIENCE.